



Reference No: 2686053A  
14  
TEKASIL ACETAT

TKK d.o.o.  
Srpenica 1  
5224 Srpenica  
Slovenija

EN 15651-1:2012: Type F: EXT-INT-CC; 20LM Sealant for façade for interior and exterior application, intended for use in cold climate.

EN 15651-2:2012: Type G-CC; 20LM Sealant used for sealing glazing applications, intended for use in cold climate.

Type F: EXT-INT		Type G	
Reaction to fire	Class E	Reaction to fire	Class E
Release of chemicals dangerous to the environment	NPD	Release of dangerous chemicals to the environment	NPD
Water tightness and air tightness		Water tightness and air tightness	
Resistance to flow	≤ 3 mm	Resistance to flow	≤ 3 mm
Loss of Volume	≤ 45 %	Loss of Volume	≤ 40 %
Adhesion / cohesion at maintained extension after water immersion	NF	Elastic recovery	≥ 40 %
Elastic recovery	≥ 60 %	Tensile properties- Secant modulus at 23°C	≤ 0,4 MPa
Tensile properties- Secant modulus at 23°C	≤ 0,4 MPa	Tensile properties- Secant modulus at -20°C	≤ 0,6 MPa
Tensile properties- Secant modulus at -20°C	≤ 0,6 MPa	Tensile properties at maintained extension	NF
Tensile properties at maintained extension	NF	Adhesion/cohesion at variable temperatures	NF
Adhesion/cohesion at variable temperatures	NF	Adhesion / cohesion at maintained extension after water immersion	NF
Durability	Pass	Adhesion/cohesion after exposure to heat, water and artificial light	NF
<b>TYPE F: EXT-INT-CC</b>		Resistance to compression	0,44 MPa
Tensile properties -secant modulus	≤ 0,9 MPa	Durability	Pass
Tensile properties at maintained extension	NF	<b>TYPE G-CC</b>	
		Tensile properties- secant modulus	≤ 0,9 MPa
		Adhesion/Cohesion at maintained extension	NF