



Reference No: 9991649595
14
TEKAFLEX MS 15

TKK d.o.o.
Srpenica 1
5224 Srpenica
Slovenija

EN 15651-1:2012: Type F: EXT-INT-CC; 20LM Sealant for façade for interior and exterior application, intended for use in cold climate.

EN 15651-4:2012: Type PW: INT; 20LM Sealant used for pedestrian walkways for interior application.

Type F: EXT-INT		Type PW: INT	
Reaction to fire	Class E	Reaction to fire	Class E
Release of chemicals dangerous to the environment	NPD	Release of dangerous chemicals to the environment	NPD
Water tightness and air tightness		Water tightness and air tightness	
Resistance to flow	≤ 3 mm	Resistance to flow	≤ 3 mm
Loss of Volume	≤ 10 %	Loss of Volume	≤ 10 %
Adhesion / cohesion at maintained extension after water immersion	NF	Elastic recovery	≥ 60 %
Elastic recovery	≥ 60 %	Tensile properties- Secant modulus at 23°C	≤ 0,4 MPa
Tensile properties- Secant modulus at 23°C	≤ 0,4 MPa	Tensile properties- Secant modulus at -20°C	≤ 0,6 MPa
Tensile properties- Secant modulus at -20°C	≤ 0,6 MPa	Tensile properties at maintained extension	NF
Tensile properties at maintained extension	NF	Adhesion/cohesion at variable temperatures	NF
Adhesion/cohesion at variable temperatures	NF	Adhesion/cohesion at maintained extension after water immersion	NF
Durability	Pass	Tear resistance	NF
TYPE F: EXT-INT-CC		Durability	Pass
Tensile properties -secant modulus	≤ 0,9 MPa		
Tensile properties at maintained extension	NF		