



EN 15651-1:2012: Type F: EXT-INT-CC; 20LM Sealant for façade for interior and exterior application, intended for use in cold climate.

EN 15651-2:2012: Type G-CC; 20LM Sealant used for sealing glazing applications, intended for use in cold climate.

EN 15651-3:2012: Type S; S1 Sealant for sanitary joints.

Type F: EXT-INT		Type G		Type S	
Reaction to fire	Class E	Reaction to fire	Class E	Reaction to fire	Class E
Release of chemicals dangerous to the environment	NPD	Release of dangerous chemicals to the environment	NPD	Release of dangerous chemicals to the environment	NPD
Water tightness and air tightness		Water tightness and air tightness		Water tightness and air tightness	
Resistance to flow	≤ 3 mm	Resistance to flow	≤ 3 mm	Resistance to flow	≤ 5 mm
Loss of Volume	≤ 45 %	Loss of Volume	≤ 40 %	Loss of Volume	≤ 55 %
Adhesion / cohesion at maintained extension after water immersion	NF	Elastic recovery	≥ 40 %	Tensile properties after water immersion	≥ 25 %
Elastic recovery	≥ 60 %	Tensile properties- Secant modulus at 23°C	≤ 0,4 MPa	Microbiological growth	0
Tensile properties- Secant modulus at 23°C	≤ 0,4 MPa	Tensile properties- Secant modulus at -20°C	≤ 0,6 MPa	Durability	Pass
Tensile properties- Secant modulus at -20°C	≤ 0,6 MPa	Tensile properties at maintained extension	NF		
Tensile properties at maintained extension	NF	Adhesion/cohesion at variable temperatures	NF		
Adhesion/cohesion at variable temperatures	NF	Adhesion / cohesion at maintained extension after water immersion	NF		
Durability	Pass	Adhesion/cohesion after exposure to heat, water and artificial light	NF		
TYPE F: EXT-INT-CC		Resistance to compression	0,40 MPa		
Tensile properties -secant modulus	≤ 0,9 MPa	Durability	Pass		
Tensile properties at maintained extension	NF	TYPE G-CC			
		Tensile properties- secant modulus	≤ 0,9 MPa		
		Adhesion/Cohesion at maintained extension	NF		