



KONTRASOL 22 V

Curing agent



Garage Koper.

FIELD OF APPLICATION

Kontrasol 22 V is an aqueous dispersion used for curing – protecting fresh concrete. It can be used on horizontal and vertical surfaces which are freshly concreted and need to be protected from the damaging effects of the sun, wind and rain. It is particularly suitable for concrete roads, airport runways, platforms, terraces and other structures where large concrete surfaces are exposed to atmospheric conditions.

Note:

If surfaces protected with **Kontrasol 22 V** need additional treatment (additional concreting, colouring, coating etc.), the hardened protective layer has to be removed mechanically (grinding, steam curing) before starting any other treatment.

CHARACTERISTICS

	Property
Appearance	white liquid
Density, 20°C	ca. 1 kg/dm ³
Viscosity, Ford 4, 20°C	20 sec.

ACTION

- **Kontrasol 22 V** covers the concrete surface with a protective layer which prevents the evaporation of water from fresh concrete because of strong sun, high temperature or drying winds and protects the concrete from heavy rain. This means that there is no need for time-consuming and expensive procedures of covering or wetting the concrete.
- **Kontrasol 22 V** is particularly suitable for hot climates. Its white colour enables a visual control of the uniformity of the covering and increases the reflection of sunbeams.

CONSUMPTION AND INSTRUCTIONS FOR USE

- Consumption: 0,20 – 0,25 kg per 1 m² of surface.
- The product is applied onto the surface by spraying (spray gun, spray for fruit trees etc.) The surface has to be free from standing water and **Kontrasol 22 V** has to be applied in a thin and uniform layer.

PACKING

- 180 kg drums and 50 kg plastic cans



KONTRASOL 22 V
Curing agent

STORAGE

- Store the product in tightly closed packaging at temperatures between +5°C and +35°C. Protect from damage, freezing and direct sunlight.
- In tightly closed and undamaged packaging, the shelf life of the product is min. 1 year from the production date.
- The product may still be used after the date of expiry, but the characteristics important for the intended use have to be examined.

SAFETY PRECAUTIONS

General instructions for working with chemicals should be observed when working with **Kontrasol 22 V**:

- Eating, drinking or smoking during work is prohibited.
- After finishing work, hands should be thoroughly washed with water.

NOTE

Instructions are given on the basis of examinations and technical experience of the firm. Due to specific conditions and work methods, preliminary tests are advised for every type of use. Since we cannot influence the course of work, we cannot be held responsible for its quality.