



KULIR TEKOČINA

Surface Retardant for Washed Concrete

FIELD OF APPLICATION

KULIRTEKOČINA is used for manufacturing concrete products with exposed aggregate.

INSTRUCTIONS FOR USE

The KULIR TEKOČINA surface retardant is available in a concentration that may be used as is, without dilution. It is suitable for the manufacture of washed concrete whereby KULIR TEKOČINA is applied to the concrete surface and not to the mould. KULIR TEKOČINA should be sprayed onto the concrete surface when there is no free surface water on it. The consumption of KULIR TEKOČINA depends on the composition of concrete, desirable effect and washing out depth. The concrete coated with KULIR TEKOČINA should be washed out after 24 hours. In case of a strong effect, the dilution of KULIR TEKOČINA with water at a ratio of 1:1 is recommended. Considering the fact that the optimal retardation time and retardation efficiency are affected by several factors, previous trials are recommended.

PACKAGING

KULIR TEKOČINA is packaged in 50 kg plastic containers.

STORAGE

If kept in tightly closed packaging, in places not exposed to high temperatures or freezing, the shelf life of KULIR TEKOČINA is 6 months.

CONSUMPTION

0,040 - 0,1 kg/m²

CAUTION

The instructions are provided on the basis of our researches and experiences and therefore, owing to special requirements, specific conditions and manner of work, previous trials are obligatory for each particular case of application.