



CEMENTOL[®] HIDROFOB M

Water-retaining admixture for earth-moist and semi-dry concretes

FIELD OF APPLICATION

Cementol Hidrofob M is a powdered admixture used for preparing cement, cement-lime and lime mortars and renders with highly reduced capillary absorption.

ACTION

Cementol Hidrofob M is an admixture with hydrophobic properties. When added to mortar or concrete, highly reduced capillary absorption is achieved.

DOSAGE AND INSTRUCTIONS FOR USE

- Dosage: 0,5 - 1,2% of binder weight (cement / cement + lime / lime).
- Dosage depends on mortar composition and required effects. Preliminary tests are advisable in order to achieve optimal effects.
- **Cementol Hidrofob M** is added to dry mortar mixture (binder and filler) and mixed well to get a uniform distribution before adding water. Attention should be paid to avoid bleeding of mortars, otherwise **Cementol Hidrofob M** - because of its hydrophobic properties - might flow onto the mortar surface.

PACKING

- 20 kg sacks

STORAGE

- The product should be stored in dry, ventilated places, protected from damage.
- In tightly closed and undamaged packaging, the shelf life of the product is min. 2 years from the production date.
- The product may still be used after the date of expiry, but the characteristics important for the intended use have to be examined.

SAFETY PRECAUTIONS

General instructions for working with chemicals should be observed when working with **Cementol Hidrofob M**:

- Eating, drinking or smoking during work is prohibited.
- After finishing work, hands should be thoroughly washed with water.

NOTE

Instructions are given on the basis of examinations and technical experience of the firm. Due to specific conditions and work methods, preliminary tests are advised for every type of use. Since we cannot influence the course of work, we cannot be held responsible for its quality.