



# TEKASOL

## Welding antiadhesive



Welding antiadhesive is cleaning and protection product for the welding process. It protects tools and welding elements from sticking of the welding splitters.

### PROPERTIES

- Offers complete protection during the welding process.
- Allows nozzles to be easily changed and cleaned.
- Prolongs the life of the welding nozzle.
- It doesn't affect the weld itself and allows further varnishing, galvanizing or chroming.

### USE

It is used for cleaning and protection in the welding proces.

### TECHNICAL DATA

State: liquid  
 Odour: characteristic (solvent like)  
 Color: amber  
 It not does contain silicone.

### APPLICATION

One or two layers are sufficient for protection of the parts to be welded. Before welding, wait a few minutes until the solvent has evaporated.

### PACKING

- aerosol can of 400 ml

### STORAGE

24 months (+10°C to +20°C).  
 Canes should be stored in upright position.

### SAFETY PRECAUTIONS

Contains Methylene Chloride.  
 Limited evidence of a carcinogenic effect. Do not breathe vapour. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas.  
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep out of the reach of children.

### ATTENTION

The information supplied is accurate to the best of our knowledge and is based on reliable tests and practical experiences. Properties quoted are intended, as a guide and do not therefore constitutes a specification. You should thoroughly test any application to be sure that product corresponds to the required performances.