

Declaration of Performance

Unique identification code of the product-type:

	TEKADOM ACRYFLEX Reference number: 2585496003
---	---

Revision: 01 15/11/2014

In Accordance with the CPR, Regulation (EU) N°305/2011

In accordance with the applicable harmonised technical specification:

- EN 15651-1:2012 : Type F: EXT-INT; 12,5P
- EN 15651-3:2012 : Type S; S1

Intended use or uses of the construction product:

- Sealant for façade for interior and exterior application.
- Sealant for sanitary joints.

System or systems of assessment and verification of constancy of performance of the construction product, as set out in Annex V:

- System 3
- System 3: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5): TKK d.o.o., Srpenica 1, 5224 Srpenica

The notified body: ZAG, NB 1404 has carried out Determination of Product Type under system 3.

Essential characteristics	Performance	Harmonised technical specification
TIP F: EXT-INT		
Reaction to fire	Class E	EN 15651-1
Release of chemicals dangerous to the environment	NPD	
Water tightness and air tightness	/	
Resistance to flow	≤ 3 mm	
Loss of Volume	≤ 25 %	
Tensile properties after water immersion	≥ 100 %	
Elastic recovery	< 40%	
Tensile properties, secant modulus at 23°C	/	
Tensile properties, secant modulus at -20°C	/	
Tensile properties at maintained extension	/	
Adhesion/cohesion at variable temperatures	/	
Durability	Pass	
Elongation at break	≥ 100 %	
Adhesion / cohesion at constant temperature	NF	
Tensile properties after water immersion: Elongation	≥ 100 %	
TIP S		
Reaction to fire	Class E	EN 15651-3
Release of chemicals dangerous to the environment	NPD	
Water tightness and air tightness		
Resistance to flow	≤ 5 mm	
Loss of Volume	≤ 55 %	
Adhesion/cohesion after water immersion	≥ 25 %	
Microbiological growth	0	
Durability	Pass	

Conditioning: method A

Substrate: mortar

"The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer."



TKK d. o. o.
Srpenica 1, 5224 Srpenica, Slovenija
T: +386 (0) 5 3841300
F: +386 (0) 5 3841390, 391
E: info@tkk.si
www.tkk.si

Signed for and on behalf of the manufacturer by:

Srpenica, 15.11.2014


Marko Štrukelj,
Product manager

Declaration of performance