

Declaration of Performance

Unique identification code of the product-type:

	TEKADOM FIRESTOP Reference number: 75757260
---	---

Revision: 01 15/04/2014

In Accordance with the CPR, Regulation (EU) N°305/2011

In accordance with the applicable harmonised technical specification:

- EN 15651-1:2012 : Type F-INT

Intended use or uses of the construction product:

- Sealant for façade for interior application.

System or systems of assessment and verification of constancy of performance of the construction product, as set out in Annex V:

- System 4
- System 3: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):
TKK d.o.o., Srpenica 1, 5224 Srpenica

The notified body: ZAG, NB 1404 has carried out Determination of Product Type under system 3.

Essential characteristics	Performance	Harmonised technical specification
TIP F: INT		EN 15651-1
Reaction to fire	Class E	
Release of chemicals dangerous to the environment		
Water tightness and air tightness		
Resistance to flow	≤ 5 mm	
Loss of Volume	≤ 45 %	
Elongation at break	≥ 25 %	
Durability	Pass	

Conditioning: method A

Substrate: mortar

"The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer."

Signed for and on behalf of the manufacturer by:



Marko Štrukelj,
Product manager

Srpenica, 15.04.2014